

Industrial Ethernet U-LINK-LIC-STD-300-1Y

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Example of use



The Weidmüller u-link remote access service is a web-based portal application to give service PCs simple and secure access to Ethernet devices in a remote network. VPN-supported remote access through a service PC is enabled with the u-link VPN server and a Weidmüller router located in the target network. The u-link VPN server acts as a central meeting point and connects a service PC (VPN client) to a router in the target network in order to reach the Ethernet devices that are connected to the router.

With the u-link VPN Server as the central meeting point server, the VPN clients (service PC and Weidmüller router) always connect outbound and thus conform to the typical IT security requirements.

Separate database and server instances are used for each u-link customer account (secure client isolation) to ensure data integrity.

Communication between the u-link VPN server and remote clients (service PCs and routers) takes place via a certificate-protected openVPN connection.

Weidmüller offers the following usage variations and additional options for the u-link Remote Access Service:

Entry version

- Free use, no runtime limitation
- Max. 50 router objects (access points to a remote network)

- 2 simultaneous VPN through-connections per customer account

Standard version 50/150/300/500/other licence models on request

- Licence-dependent configuration from 50 up to 500 router objects (further license models on request)
- Extensive functional and performance features as compared with the entry version, such as
 - 3 simultaneous VPN through-connections per customer account (can be extended)
 - China-VPN: reliable VPN connection to and from China
 - Firmware management: Display of firmware status of all routers and the option of a time-controlled, automated firmware update
 - Individual access rights: granular configuration of access rights to devices in the target network
 - Extensive event log: Presentation of all activities in the u-link portal with extensive filter and export functions
 - Password policy: Increased security through configurable specification of minimum requirements for password quality and validity period

"Additional VPN connections" extension

- Licence code can be used with all standard versions
- Additional data volume with guaranteed bandwidth

Data sheet

General ordering data

Type	U-LINK-LIC-STD-300-1Y
Order No.	2457840000
Version	"Standard 300" version software licence for u-link Remote Access Service. Can be used to upgrade an entry version or "Standard 150" version or to extend the period of a "Standard 300" version"
GTIN (EAN)	4050118472844
Qty.	1 pc(s).

**Industrial Ethernet
U-LINK-LIC-STD-300-1Y**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Net weight 73 g

Functions and features

China-VPN	Reliable VPN connection to and from China	Device management	Illustration of the device infrastructure (remote access objects) in a clearly defined tree structure via location, group and device objects
Firmware management	Display of the firmware version of all routers and the possibility of timed, automated firmware updates	Monthly data volume and bandwidth	<= 5 GB with max. 1 Mbit/s, > 5 GB with max. 500 Kbit/s. Increase by 1 GB/month with 1 Mbit/s per added-on pass-through VPN connection, for data volume > 12 GB/month max. 500 Kbit/s
Number of configurable router objects (access points remote network)	300 (can be extended using Standard 500 licences), additional license models available on request	Number of configurable user objects (service PC)	Unrestricted
Password guideline	Increased security through configurable specification of minimum requirements for the password quality and validity period	Period	1 year from activation of the licence key. When extending a "Standard 300" version, the validity period is extended by 1 year from the expiry date of the current period, but not less than 1 year., Note: Where the validity period has expired, the bandwidth is automatically reduced to the values used with the free entry version (<= 1 GB with max. 500 kbit/s, > 1 GB with max. 64 kbit/s)
Simultaneously usable pass-through VPN connections	3 (can be extended by adding on other pass-through VPN connections)	System availability	≥ 99.6%
Usage information	Extended reporting and statistical information (itemised statement, usage duration, data volume)	User organisation	Organisation of service users in groups, assignment of selective access rights to device topology, group-dependent assignment of rights re. device configuration and user administration

System requirements

Hardware (service PC)	PC with operating system Windows 7, 8 or 10	Hardware, remote target network	Weidmüller router (except IE-SR-2GT-LAN-FN; 1489940000), u-link VPN access integrated in firmware (from V3.0.1)
Portal administration (user/device configuration)	Standard browser (IE, Edge, Chrome, Firefox) via an HTTPS connection (SSL), login via username and password	VPN software (service PC)	u-link VPN-client (installation on PC)

Creation date May 2, 2020 1:48:41 PM CEST

Data sheet

Industrial Ethernet U-LINK-LIC-STD-300-1Y

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Miscellaneous

Activation	Client account administrator enters the licence key in the u-link portal (functions immediately available)	Included in delivery	Letter with licence key
------------	--	----------------------	-------------------------

Classifications

ETIM 6.0	EC000809	ETIM 7.0	EC000809
eClass 9.0	27-24-25-01	eClass 9.1	27-24-25-01
eClass 10.0	27-24-25-01		

Downloads

Software	u-link VPN-Client - Version 2.0.194
User Documentation	u-link Technical User Guide

Industrial Ethernet U-LINK-LIC-STD-300-1Y

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Accessories

Industrial Security Router



High performance industrial-security router

- Variations with 2 or 6 Gigabit ports
 - NAT masquerading, 1:1 network mapping and port forwarding
 - VPN function (u-link Remote Access Service, OpenVPN and IPsec)
 - Key switch function to control a WAN/VPN connection
-
- 6-port variations with expanded routing functionality
 - Variations with integrated 4G/LTE modem for high-speed, internet-based mobile communications access
 - Cost-efficient variation without VPN functionality for NAT and security applications (1489940000, IE-SR-2GT-LAN-FN)
 - Variations with DNV-GL approval for use in a maritime environment

General ordering data

Type	IE-SR-2GT-LTE/4G-US	Version
Order No.	2535780000	Security/NAT/VPN/U-link Router, with integrated LTE / 4G modem,
GTIN (EAN)	4050118547597	US model, Gigabit Ethernet, 2x RJ45 10/100/1000BaseT(X), IP20,
Qty.	1 pc(s).	-20 °C...70 °C
Type	IE-SR-2GT-LTE/4G-EU	Version
Order No.	2535930000	Security/NAT/VPN/U-link Router, with integrated LTE / 4G modem,
GTIN (EAN)	4050118547603	EU model, Gigabit Ethernet, 2x RJ45 10/100/1000BaseT(X), IP20,
Qty.	1 pc(s).	-20 °C...70 °C
Type	IE-SR-6GT-LTE/4G-EU	Version
Order No.	2535960000	Security/NAT/VPN/U-link Router, with integrated LTE / 4G modem,
GTIN (EAN)	4050118547634	EU model, Gigabit Ethernet, 6 * RJ45 10/100/1000BaseT(X), IP20,
Qty.	1 pc(s).	-20 °C...70 °C
Type	IE-SR-2GT-UMTS/3G	Version
Order No.	1345250000	Security/NAT/VPN/U-link Router, with integrated UMTS / 3G modem,
GTIN (EAN)	4050118149715	Gigabit Ethernet, 2x RJ45 10/100/1000BaseT(X), IP20, -20 °C...70 °C
Qty.	1 pc(s).	°C
Type	IE-SR-2GT-LAN	Version
Order No.	1345270000	Security/NAT/VPN/U-link Router, Gigabit Ethernet, 2 * RJ45
GTIN (EAN)	4050118149807	10/100/1000BaseT(X), IP20, -20 °C...70 °C
Qty.	1 pc(s).	
Type	IE-SR-6GT-LTE/4G-US	Version
Order No.	2535950000	Security/NAT/VPN/U-link Router, with integrated LTE / 4G modem,
GTIN (EAN)	4050118547627	US model, Gigabit Ethernet, 6 * RJ45 10/100/1000BaseT(X), IP20,
Qty.	1 pc(s).	-20 °C...70 °C

Data sheet**Industrial Ethernet
U-LINK-LIC-STD-300-1Y**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Accessories

Type	IE-SR-6GT-LAN	Version
Order No.	2535940000	Security/NAT/VPN/U-link Router, Gigabit Ethernet, 6 * RJ45
GTIN (EAN)	4050118547610	10/100/1000BaseT(X), IP20, -20 °C...70 °C
Qty.	1 pc(s).	