

**HSS-HF 4.8-9.5 EL SW30M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



The continuous shrink sleeves of the MultiMark series are printed in seconds using our thermo-transfer printers. The length of the marker can be individually adjusted to suit the number of characters or available space. The required length is pre-perforated precisely using a special blade. With their oval shape the markers can be opened easily, applied quickly and shrunk precisely to fit the conductor. An external reel holder (1302920000) has to be used for reels above 30 m printing material.

**General ordering data**

|                    |  |
|--------------------|--|
| Type               | HSS-HF 4.8-9.5 EL SW30M  |
| Order No.          | <a href="#">2518950000</a>   |
| Version            | Conductor and cable markers, 4.8 - 9.5 mm, x 15.1 mm, black                      |
| GTIN (EAN)         | 4050118531152  |
| Qty.               | 1 pc(s).   |
| compatible printer | <a href="#">2599430000</a> <a href="#">2599440000</a> <a href="#">1140490000</a> |

Creation date May 2, 2020 8:10:19 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

## HSS-HF 4.8-9.5 EL SW30M

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

## Technical data

### Dimensions and weights

|            |           |                 |              |
|------------|-----------|-----------------|--------------|
| Length     | 30,000 mm | Length (inches) | 1,181.1 inch |
| Width      | 15.1 mm   | Width (inches)  | 0.594 inch   |
| Depth      | 1.2 mm    | Depth (inches)  | 0.047 inch   |
| Net weight | 548 g     |                 |              |

### General data

|                 |           |                             |               |
|-----------------|-----------|-----------------------------|---------------|
| Colour          | black     | Halogen                     | No            |
| Length          | 30,000 mm | Material                    | Polyolefine   |
| Number per roll | 1         | Operating temperature range | -55... 105 °C |
| Width           | 15.1 mm   |                             |               |

### Conductor and cable markers

|                               |                   |                                   |                    |
|-------------------------------|-------------------|-----------------------------------|--------------------|
| Conductor O.D.                | 4.8 - 9.5 mm      | Conductor O.D., max.              | 9.5 mm             |
| Conductor O.D., min.          | 4.8 mm            | Conductor cross-section, max.     | 16 mm <sup>2</sup> |
| Conductor cross-section, min. | 4 mm <sup>2</sup> | Halogen                           | No                 |
| Rate of shrinkage             | 2:1               | Recommended shrinking temperature | 90 °C              |

### Classifications

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0   | EC001530    |
| eClass 9.0  | 27-40-04-01 | eClass 9.1 | 27-40-04-01 |
| eClass 10.0 | 27-40-04-01 |            |             |

### Product information

Product information External roll holder 1302920000 necessary

### Approvals

ROHS Conform

### Downloads


|   |   |
|---|---|
| Approval/Certificate/Document of Conformity | <a href="#">NFX 70-100-1 2006 + NF X 70-100-2 2006</a><br><a href="#">BS EN 45545-2 2013+A1 2015</a><br><a href="#">BS EN ISO 4589-2 1999</a> |
| Engineering Data                            | <a href="#">EPLAN</a>   |

**Data sheet**

**HSS-HF 4.8-9.5 EL SW30M**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**



**HSS-HF 4.8-9.5 EL SW30M**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Accessories****Accessories / replacement parts**

Our marking systems can be used to quickly and reliably label connector markers, conductor and cable markers, device markers and labels. The M-Print® PRO software enables rapid and easy identification of your electrical equipment. You can design, label and order your marking materials professionally and quickly. Frames, barcodes, graphics or photos are easily incorporated. The versatile data conversion routines enable quick and flexible data integration. The Weidmüller PrintJet ADVANCED, MCP Plus and MCP Basic printers and the THM series printers are available for printing.

**General ordering data**

Type THM MMP ROLLER 25  
Order No. [1357430000](#)  
GTIN (EAN) 4050118160253  
Qty. 1 pc(s).

Type THM MMP ROLLER 115  
Order No. [1357420000](#)  
GTIN (EAN) 4050118160314  
Qty. 1 pc(s).

Type MM PLUS ROLLER 110  
Order No. [2672590000](#)  
GTIN (EAN) 4050118708097  
Qty. 1 pc(s).

**HSS-HF 4.8-9.5 EL SW30M**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Accessories**

**THM MULTIMARK**



**MMP**

The only printer you need for your marking tasks The THM MMP is a compact and modular thermal transfer printer that fully demonstrates its many advantages and high number of potential uses. The integrated cutting and perforation option enables continuous materials to be cut to any length – making your work considerably easier when it comes to cutting and assigning the respective labels. The printer edits markers and labels from the MultiMark family as well as continuous materials, textile and polyester labels, shrink-fit sleeves and PLC labels.

**Your benefits with MultiMark**

- One printer for all jobs
- Ideal for small and medium print volumes
- Nearly maintenance-free thanks to thermal transfer technology
- Good legibility (resolution: 300 dpi)
- Flexibility thanks to modular perforation and cutting unit
- The print roller can be changed in 30 seconds
- High output, 250 Dekafix markers/min.

**General ordering data**

|            |                            |
|------------|----------------------------|
| Type       | THM MMP EXT.RH             |
| Order No.  | <a href="#">1302920000</a> |
| GTIN (EAN) | 4050118102307              |
| Qty.       | 1 pc(s).                   |

**Ink ribbons THM MMP**



These printers produce excellent printing results thanks to the thermal transfer technique. Different materials and the user-friendly printing system under Windows optimise marking efforts.

**General ordering data**

|            |                            |            |
|------------|----------------------------|------------|
| Type       | RIBBON MM 84/300 WS        | Version    |
| Order No.  | <a href="#">2005040000</a> | Ink ribbon |
| GTIN (EAN) | 4050118390025              |            |
| Qty.       | 1 pc(s).                   |            |