

VPU series
VPU PV I+II 0 1500

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Product image**Type II surge voltage arrester for use in photovoltaic applications**

- Pluggable arrester
- Suitable for protecting DC systems
- High energy absorption with short response time
- Tested in accordance with EN 50539-11
- Suitable for use in accordance with IEC 60364-7-712 / EN 50539-12
- Coded voltage level
- Installation in distribution board
- Thermal protection function

General ordering data

Type	VPU PV I+II 0 1500
Order No.	2530570000
Version	Surge voltage arrester, Low voltage, Accessories, 1500 V, Spare arrester, 30 kA, I _{imp} : 5 kA
GTIN (EAN)	4050118540482
Qty.	1 pc(s).

VPU series
VPU PV I+II 0 1500
Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Width	18 mm	Width (inches)	0.709 inch
Height	45 mm	Height (inches)	1.772 inch
Depth	79 mm	Depth (inches)	3.11 inch
Net weight	70 g		

Temperatures

Humidity	5 - 95% rel. humidity	Operating temperature, max.	70 °C
Operating temperature, min.	-40 °C	Storage temperature, max.	85 °C
Storage temperature, min.	-40 °C	Operating temperature	-40 °C...70 °C
Storage temperature	-40 °C...85 °C		

Rated data UL

Voltage type	DC	Certificate No. (cURus)	E354261
Certificate No. (UR)	E354261	Ambient temperature (operational), min.	-40 °C
Ambient temperature (operational), max.	85 °C	Rated Voltage U_N	750 V
SCCR	65 kA	I_n	20 kA
Category	SPD TYPE 1CA	Rated current (UL)	1,500 A
Altitude	< 4,000 m, see operating instructions		

General data

Altitude	< 4,000 m, see operating instructions	Colour	orange
Optical function display	green = OK; red = arrester is defective - replace	Protection degree	IP20
UL 94 flammability rating	V-0	Version	Spare arrester

Insulation coordination acc. to EN 50178

Pollution severity	2	Surge voltage category	III
--------------------	---	------------------------	-----

Photovoltaic technical data

Discharge current I_n (8/20 μ s)	20 kA	Discharge current, max. (8/20 μ s)	30 kA
Lightning test current I_{imp} (10/350 μ s)	5 kA	PV system voltage, max. U_{cpv}	1,500 V
Protection level U_p mode (+/-, -/PE, +/- PE)	$\leq 5,0$ kV	Protection level U_p mode (+/-)	$\leq 5,0$ kV
Protection level U_p mode (-/PE)	$\leq 5,0$ kV	Protection level U_p mode(+/PE)	$\leq 5,0$ kV
Requirements class	Type I/II	Short-circuit current I_{SCPv}	11,000 A
Standards	EN 50539-11:2013+A1:2014, UL 1449 Ed.4	Standby power consumption P_c	< 0.2 W
Total discharge current I_{total} (8/20 μ s)	40 kA	Total discharge current I_{total} (10/350 μ s)	10 kA

Connection data

Type of connection	pluggable
--------------------	-----------

Data sheet

**VPU series
VPU PV I+II 0 1500**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Classifications

ETIM 6.0	EC000941	ETIM 7.0	EC000941
eClass 9.0	27-13-08-05	eClass 9.1	27-13-08-05
eClass 10.0	27-13-08-05	UNSPSC	30-21-19-21

Approvals

Approvals



ROHS Conform

Downloads

Approval/Certificate/Document of Conformity [EAC VPU SERIES](#)
[CE VPU PV](#)

Data sheet

VPU series
VPU PV I+II 0 1500

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Electric symbol

