

VPU series
VPU PV I+II 0M 1500

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Product image**Type II surge voltage arrester for use in photovoltaic applications**

- Pluggable arrester
- Suitable for protecting DC systems
- High energy absorption with short response time
- Tested in accordance with EN 50539-11
- Suitable for use in accordance with IEC 60364-7-712 / EN 50539-12
- Coded voltage level
- Installation in distribution board
- Thermal protection function

General ordering data

| | |
|------------|--|
| Type | VPU PV I+II 0M 1500 |
| Order No. | 2534330000 |
| Version | Surge voltage arrester, Low voltage, Accessories, 1500 V, Spare arrester, 30 kA, I _{imp} : 5 kA |
| GTIN (EAN) | 4050118546002 |
| Qty. | 1 pc(s). |

VPU series

VPU PV I+II 0M 1500

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|-------|-----------------|------------|
| Width | 18 mm | Width (inches) | 0.709 inch |
| Height | 45 mm | Height (inches) | 1.772 inch |
| Depth | 79 mm | Depth (inches) | 3.11 inch |
| Net weight | 67 g | | |

Temperatures

| | | | |
|-----------------------------|-----------------------|-----------------------------|----------------|
| Humidity | 5 - 95% rel. humidity | Operating temperature, max. | 70 °C |
| Operating temperature, min. | -40 °C | Storage temperature, max. | 85 °C |
| Storage temperature, min. | -40 °C | Operating temperature | -40 °C...70 °C |
| Storage temperature | -40 °C...85 °C | | |

Rated data UL

| | | | |
|---|---------------------------------------|---|---------|
| Voltage type | DC | Certificate No. (cURus) | E354261 |
| Certificate No. (UR) | E354261 | Ambient temperature (operational), min. | -40 °C |
| Ambient temperature (operational), max. | 85 °C | Rated Voltage U_N | 1,500 V |
| SCCR | 65 kA | I_n | 20 kA |
| Category | SPD TYPE 1CA | Rated current (UL) | 1,500 A |
| Altitude | < 4,000 m, see operating instructions | | |

General data

| | | | |
|---------------------------|---|-------------------|----------------|
| Altitude | < 4,000 m, see operating instructions | Colour | orange |
| Optical function display | green = OK; red = arrester is defective - replace | Protection degree | IP20 |
| UL 94 flammability rating | V-0 | Version | Spare arrester |

Insulation coordination acc. to EN 50178

| | | | |
|--------------------|---|------------------------|-----|
| Pollution severity | 2 | Surge voltage category | III |
|--------------------|---|------------------------|-----|

Photovoltaic technical data

| | | | |
|--|--|--|---------------|
| Discharge current I_n (8/20 μ s) | 20 kA | Discharge current, max. (8/20 μ s) | 30 kA |
| Lightning test current I_{imp} (10/350 μ s) | 5 kA | PV system voltage, max. U_{cpv} | 1,500 V |
| Protection level U_p mode (+/-, -/PE, +/- PE) | $\leq 5,0$ kV | Protection level U_p mode (+/-) | $\leq 5,0$ kV |
| Protection level U_p mode (-/PE) | $\leq 5,0$ kV | Protection level U_p mode(+/PE) | $\leq 5,0$ kV |
| Requirements class | Type I/II | Short-circuit current I_{SCPv} | 11,000 A |
| Standards | EN 50539-11:2013+A1:2014, UL 1449 Ed.4 | Standby power consumption P_c | < 0.2 W |
| Total discharge current I_{total} (8/20 μ s) | 40 kA | Total discharge current I_{total} (10/350 μ s) | 10 kA |

Connection data

| | |
|--------------------|-----------|
| Type of connection | pluggable |
|--------------------|-----------|

Data sheet

VPU series
VPU PV I+II 0M 1500

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC000941 | ETIM 7.0 | EC000941 |
| eClass 9.0 | 27-13-08-05 | eClass 9.1 | 27-13-08-05 |
| eClass 10.0 | 27-13-08-05 | UNSPSC | 30-21-19-21 |

Approvals

Approvals



ROHS Conform

Downloads

Approval/Certificate/Document of Conformity [EAC VPU SERIES](#)
[CE VPU PV](#)

Data sheet

VPU series
VPU PV I+II 0M 1500

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Electric symbol

