

**Automation Products - u-view
UV66-ADV-10-CAP-W**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Product image

Convenient touch panels make it easy to monitor and control machines and systems.

u-view touch panels from Weidmüller offer excellent image quality and can be used in an industrial environment without any restrictions.

The basic product line features resistive single-touch panels with a diagonal of 7" or 10.1" and the advanced line features capacitive multi-touch panels with a diagonal of 7", 10.1", or 15.6".

All panels are equipped with a Linux operating system using a HTML5-capable browser and are optimized for web-applications due to the integrated kiosk mode and their easy configuration.

As a result, they are the perfect solution for web-based visualisations and allow access to different webservers, for example u-create PROCON-WEB, u-control web and many more.

The panels have a particularly flat design, with a robust aluminium IP66 housing.

General ordering data

Type	UV66-ADV-10-CAP-W
Order No.	2555840000
Version	web-compatible touch panel, Display size 10.1", MultiTouch, Capacitive, Front protection IP66
GTIN (EAN)	4050118566208
Qty.	1 pc(s).

**Automation Products - u-view
UV66-ADV-10-CAP-W**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

Width	293 mm	Width (inches)	11.535 inch
Height	201.5 mm	Height (inches)	7.933 inch
Depth	48 mm	Depth (inches)	1.89 inch
Net weight	2,350 g		

Temperatures

Humidity	80 % relative humidity (without condensation)	Operating temperature	0 °C ... +50 °C
Storage temperature	-20 °C ... +60 °C		

System data

Interface	2 x Ethernet 10/100/1000 MBit/s (RJ45), 2 x USB 2.0 (host), 1 x serial RS-232/RS-485/ RS-422	Memory (Flash)	4 GB
Operating system	Linux + Browser (HTML5)	Processor	ARM Cortex A9 1 GHz NXP® i.MX6 DualLite
RAM	1 GB		

Equipment

Angle (horizontal)	Left: 85° / Right: 85°	Angle (vertical)	Top: 85° / Bottom: 85°
Luminance	400 cd/m ²	Material display	Glass
Material frame	metal	Number of displayable colours	16 M
Resolution	1280 x 800	Size	10.1 "
Touch-Screen	MultiTouch, capacitive		

General data

Protection degree	IP66	Voltage supply	24 V DC
-------------------	------	----------------	---------

Classifications

ETIM 6.0	EC001412	ETIM 7.0	EC001412
eClass 9.0	27-33-02-01	eClass 9.1	27-33-02-01
eClass 10.0	27-33-02-01		

Approvals

Approvals



ROHS Conform

Downloads

Engineering Data	STEP
Software	Update process to 1.0.0.6
User Documentation	QGUI UC20 HMI

Creation date May 2, 2020 5:36:43 AM CEST