

**Cabtite (cable entry system)  
CABTITE CR 16/8 EMV**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



The Cabtite cable entry system offers maximum flexibility in the cable management of control cabinets, enclosures and machines, while at the same time saving time, as well as providing secure sealing and strain relief for pre-terminated and non-terminated cables. Cabtite's modular design of frame, grid inlays and sealing elements enables rapid configuration of cut-outs for pre-terminated cables - without the use of tools and with a reliable sealing of IP66 according to DIN EN 60529. Frame. Inlay. Sealing element. Three basic components in the modular system guarantee highest flexibility, variability and diversity of variants.

**General ordering data**

Type	CABTITE CR 16/8 EMV
Order No.	<a href="#">2583910000</a>
Version	Cable protection strips, Cabtite (cable entry system), Steel, galvanized, silver, Height: 35.23 mm, Width: 113 mm, Depth: 16 mm
GTIN (EAN)	4050118647051
Qty.	10 pc(s).

## Data sheet

### Cabtite (cable entry system) CABTITE CR 16/8 EMV

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Width	113 mm	Width (inches)	4.449 inch
Height	35.23 mm	Height (inches)	1.387 inch
Depth	16 mm	Depth (inches)	0.63 inch
Mounting dimension - width	5.3 mm	Mounting dimension - height	5.91 mm
Net weight	40.8 g	Diameter	5.3 mm

### General information

Halogen	No	Silicone	No
Material	Steel, galvanized		

### Classifications

ETIM 6.0	EC002624	ETIM 7.0	EC002624
eClass 9.0	27-18-28-15	eClass 9.1	27-18-92-65
eClass 10.0	27-18-28-15		

### Approvals

ROHS	Conform
------	---------

### Downloads

Engineering Data	<a href="#">EPLAN</a>
Engineering Data	<a href="#">STEP</a>