# PAC
# PAC-UNIV-HE20-1:1-4M

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Similar to illustration

Cable preconfeccionado cable plano según IEC-603/ DIN41651.

- Cable plano - cable plano
- Cable plano - punteras

## General ordering data

| | |
|---|---|
| Type | PAC-UNIV-HE20-1:1-4M |
| Order No. | 7789301040 |
| Version | Pre-assembled cable, PAC, Cable LiYY, 0.25 mm² |
| GTIN (EAN) | 8430243968805 |
| Qty. | 1 pc(s). |

# PAC
# PAC-UNIV-HE20-1:1-4M

**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

## Technical data

### Dimensions and weights

| | |
|---|---|
| Net weight | 444 g |

### Temperatures

| | | | |
|---|---|---|---|
| Operating temperature, max. | 50 °C | Operating temperature, min. | -10 °C |
| Storage temperature, max. | 60 °C | Storage temperature, min. | -10 °C |
| Operating temperature | -10...50 °C | Storage temperature | -10...60 °C |

### Environmental Product Compliance

| | |
|---|---|
| REACH SVHC | Lead 7439-92-1 |

### General Data

| | | | |
|---|---|---|---|
| Connector PLC side | FLAT CABLE CONECTOR HE10 20P | Interface connector | FLAT CABLE CONECTOR HE10 20P |
| Number of poles, min. | 20-pole | Outer diameter | 8.6 ± 1 mm |
| Cable | Cable LiYY | Cable length | 4 m |
| Material | PVC | Wire cross-section | 0.25 mm² |

### Electrical Data

| | | | |
|---|---|---|---|
| Rated voltage (text) | ≤ 60 Vdc ≤ 25 Vac | Permissible current strength per path, max. | 1 A |
| Total current, max. | 3 A | Resistance | ≤ 80 mΩ/m |
| High voltage test | 1 KV/1s | | |

### Classifications

| | | | |
|---|---|---|---|
| ETIM 6.0 | EC000237 | ETIM 7.0 | EC000237 |
| eClass 9.0 | 27-24-22-20 | eClass 9.1 | 27-24-22-20 |
| eClass 10.0 | 27-24-22-20 | | |

### Approvals

| | |
|---|---|
| ROHS | Conform |