

PAC
PAC-XIOC-HE20-V0-2M0**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Similar to illustration

The pre-assembled PAC cables establish an electrical and logical connection between the PLC and the PLC interfaces. These cables consist of the following components:

- Manufacturer's PLC connector.
- Multi-pole LIYY or LY YCY cable (shielded) with a cross-section of 0.14 mm² or 0.25 mm².
- Flat cable connector, SUB-D or RSV, for connection to the interface.

The cables are tested automatically for their continuity and insulation to guarantee the functionality for which they have been designed.

General ordering data

Type	PAC-XIOC-HE20-V0-2M0
Order No.	7789862020
Version	Pre-assembled cable, PAC, Cable LiYY, 0.25 mm ²
GTIN (EAN)	4032248176489
Qty.	1 pc(s).

Creation date May 1, 2020 9:29:43 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

Data sheet

PAC PAC-XIOC-HE20-V0-2M0

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Net weight 378 g

Temperatures

Operating temperature, max.	50 °C	Operating temperature, min.	-10 °C
Storage temperature, max.	60 °C	Storage temperature, min.	-10 °C
Operating temperature	-10...50 °C	Storage temperature	-10...60 °C

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

General Data

Connector PLC side	Moeller XIOC	Interface connector	FLAT CABLE CONECTOR HE10 20P
Number of poles, min.	20-pole	Cable	Cable LiYY
Cable length	2 m	Material	PVC
Wire cross-section	0.25 mm ²		

Electrical Data

Permissible current strength per path, max.	1 A	Total current, max.	3 A
Resistance	≤ 80 mΩ/m	High voltage test	1 KV/1s

Classifications

ETIM 6.0	EC000237	ETIM 7.0	EC000237
eClass 9.0	27-24-22-20	eClass 9.1	27-24-22-20
eClass 10.0	27-24-22-20		

Approvals

Approvals



ROHS Conform