

**FPL 4G1.5C4/Q8MW/5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Take advantage of our pre-assembled FieldPower® connectors with HQ connectors acc. to IEC 23570 (DESINA) for connecting decentralised motor controller devices quickly and conveniently.

**General ordering data**

|            |   |
|------------|---|
| Type       | FPL 4G1.5C4/Q8MW/5  |
| Order No.  | <a href="#">8000005241</a>  |
| Version    | FieldPower®, Cable, Metal housing, Number of wires: 4, Ölflex Servo 709 CY 4G1.5 + 2x(2x0.75), Cross-section: 1.5 mm <sup>2</sup> , 5 m |
| GTIN (EAN) | 4032248997732   |
| Qty.       | 1 pc(s).  |

Creation date May 1, 2020 8:25:47 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

**FPL 4G1.5C4/Q8MW/5**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

|            |     |
|------------|-----|
| Net weight | 1 g |
|------------|-----|

**Environmental Product Compliance**

|            |  |
|------------|--|
| REACH SVHC | Lead 7439-92-1,<br>Potassium perfluorobutane<br>sulfonate 29420-49-3 |
|------------|--|

**General data**

|                              |   |                                  |                     |
|------------------------------|---|----------------------------------|---------------------|
| Bending radius, min., moving | 222 mm                                    | Bending radius, min., stationary | 88,8 mm             |
| Cable length, string 1       | 5 m                                       | Cross-section                    | 1.5 mm <sup>2</sup> |
| Line type                    | Ölflex Servo 709 CY 4G1.5<br>+ 2x(2x0.75) | Number of wires                  | 4                   |
| Wire assignments             | see picture                               |                                  |                     |

**Pre-assembly page 1**

|              |      |
|--------------|------|
| Connection 1 | Open |
|--------------|------|

**Pre-assembly page 2**

|              |          |
|--------------|----------|
| Connection 2 | HQ8 plug |
|--------------|----------|

**Technical data**

|               |     |
|---------------|-----|
| Rated voltage | 500 |
|---------------|-----|

**Classifications**

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC001578    | ETIM 7.0   | EC003250    |
| eClass 9.0  | 27-06-20-11 | eClass 9.1 | 27-06-90-90 |
| eClass 10.0 | 27-06-01-06 |            |             |

**Approvals**

Approvals



|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

Approval/Certificate/Document of  
 Conformity [FieldPower](#)

**FPL 4G1.5C4/Q8MW/5**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

