

**FPL 4G2.5/P/Q4MG/5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Take advantage of our pre-assembled FieldPower® connectors with HQ connectors acc. to IEC 23570 (DESINA) for connecting decentralised motor controller devices quickly and conveniently.

**General ordering data**

Type	FPL 4G2.5/P/Q4MG/5
Order No.	<a href="#">8000005295</a>
Version	FieldPower®, Cable, Metal housing, Number of wires: 4, Ölflex Classic 110 4G2.5 or similar, Cross-section: 2,5 mm <sup>2</sup> , 5 m
GTIN (EAN)	4032248997619
Qty.	1 pc(s).

Creation date May 1, 2020 8:25:00 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

**FPL 4G2.5/P/Q4MG/5****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Technical data****Dimensions and weights**

Net weight 1,147 g

**Environmental Product Compliance**REACH SVHC Lead 7439-92-1,  
Potassium perfluorobutane  
sulfonate 29420-49-3**General data**

Bending radius, min., moving	133.5 mm	Bending radius, min., stationary	35,6 mm
Cable length, string 1	5 m	Cross-section	2.5 mm <sup>2</sup>
Halogen	Yes	Line type	Ölflex Classic 110 4G2.5 or similar
Number of wires	4	Temperature range, moving, max.	70 °C
Temperature range, moving, min.	-5 °C	Temperature range, stationary, max.	70 °C
Temperature range, stationary, min.	-40 °C	Wire assignments	see picture

**Pre-assembly page 1**

Connection 1 PTS4

**Pre-assembly page 2**

Connection 2 HQ4 socket

**Technical data**

Rated voltage 500

**Classifications**

ETIM 6.0	EC001576	ETIM 7.0	EC001576
eClass 9.0	27-06-04-02	eClass 9.1	27-06-91-90
eClass 10.0	27-06-04-02		

**Approvals**

Approvals



ROHS Conform

**Downloads**Approval/Certificate/Document of  
Conformity [FieldPower](#)

**Data sheet**

**FPL 4G2.5/P/Q4MG/5**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Drawings**

