

**FPL 4G2.5/Q8KW/10****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Take advantage of our pre-assembled FieldPower® connectors with HQ connectors acc. to IEC 23570 (DESINA) for connecting decentralised motor controller devices quickly and conveniently.

**General ordering data**

Type	FPL 4G2.5/Q8KW/10
Order No.	<a href="#">8000011744</a>
Version	FieldPower®, Cable, Plastic housing, Number of wires: 4, Ölflex Classic 110 4G2.5 or similar, Cross-section: 2.5 mm <sup>2</sup> , 10 m
GTIN (EAN)	4050118238273
Qty.	1 pc(s).

Creation date May 1, 2020 8:19:24 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

**Data sheet**

**FPL 4G2.5/Q8KW/10**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

Net weight 1 g

**Environmental Product Compliance**

REACH SVHC Lead 7439-92-1,  
 Potassium perfluorobutane  
 sulfonate 29420-49-3

**General data**

Cable length, string 1	10 m	Cross-section	2.5 mm <sup>2</sup>
Line type	Ölflex Classic 110 4G2.5 or similar	Number of wires	4

**Technical data**

Rated current	16 A	Rated voltage	500 V
Rated voltage U0	300 V		

**Classifications**

ETIM 6.0	EC001578	ETIM 7.0	EC003250
eClass 9.0	27-06-20-11	eClass 9.1	27-06-90-90
eClass 10.0	27-06-01-06		

**Approvals**

Approvals



ROHS Conform

**FPL 4G2.5/Q8KW/10**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Drawings**

**Pin assignments**

	Pin	Conductor	Assignment
8 - nc	1	1	U
	2	-	-
5 - nc	3	3	W
	4	-	-
PE	5	-	-
	6	-	-
3 - W	7	2	V
	8	-	-
2 - nc	PE	gr./yell.	PE

