

**MICRO-Interface  
MI8A-I/O S SUBD15B**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Specific adapter to be connected to the MICROSERIE RELAYS using a 10-pole flat-cable connector or 15-pole Sub-D connector.

**General ordering data**

Type	MI8A-I/O S SUBD15B
Order No.	<a href="#">8800220000</a>
Version	Adapter, MICRO-Interface, IEC 60603/DIN41612 plug-in connectors, Screw connection
GTIN (EAN)	4032248497157
Qty.	10 pc(s).

Creation date May 1, 2020 6:25:17 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

**MICRO-Interface  
MI8A-I/O S SUBD15B**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Length	32 mm	Length (inches)	1.26 inch
Width	61 mm	Width (inches)	2.402 inch
Height	42 mm	Height (inches)	1.654 inch
Net weight	31.8 g		

**Temperatures**

Operating temperature, max.	50 °C	Operating temperature, min.	0 °C
Storage temperature, max.	85 °C	Storage temperature, min.	-20 °C
Operating temperature	0...50 °C	Storage temperature	-20...85 °C

**Environmental Product Compliance**

REACH SVHC	Potassium perfluorobutane sulfonate 29420-49-3
------------	--

**Connection data**

Connection on control side	IEC 60603/DIN41612 plug-in connectors	Number of poles (control side)	15-pole female
Voltage supply	max. 30 V AC/DC		

**Ratings data**

Operating voltage	30 V UC	Max. current per channel	0.5 A
Total operating current	2 A		

**Insulation coordination (EN50178)**

According to	DIN EN 50178	Rated insulation voltage	< 50 V AC
Surge voltage category	III	Pollution severity level	2
Insulation test voltage	0.35 kVAC		

**Supply connection**

Type of connection	Screw connection
--------------------	------------------

**Classifications**

ETIM 6.0	EC002584	ETIM 7.0	EC002584
eClass 9.0	27-33-02-92	eClass 9.1	27-24-22-92
eClass 10.0	27-33-02-92	UNSPSC	30-21-18-01

**Approvals**

Approvals



ROHS

Conform

**Data sheet**

**MICRO-Interface  
MI8A-I/O S SUBD15B**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**

**Downloads**

Engineering Data

[EPLAN](#)