

**Industrial Ethernet
IE-C7BS8VG-MW**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Bulk stock, copper cable, rigid, 4 x 2 x AWG 23/1, Cat. 7,
green

General ordering data

Type	IE-C7BS8VG-MW
Order No.	8955360000
Version	Installation cable, Cat.7 (ISO/IEC 11801), PVC, Products sold by meter, from 110 m
GTIN (EAN)	4032248753192
Qty.	1 m

Creation date May 1, 2020 4:16:56 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

**Industrial Ethernet
IE-C7BS8VG-MW**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

Net weight	6.5 g	Insulation cross-section	1.4 mm
------------	-------	--------------------------	--------

Temperatures

Operating temperature, max.	80 °C	Operating temperature, min.	-40 °C
Storage temperature, max.	80 °C	Storage temperature, min.	-40 °C
Operating temperature	-40 °C...80 °C	Storage temperature	-40 °C...80 °C
Installation temperature	-15 °C...60 °C		

Cable specific standards

Corrosiveness of fumes	to IEC 60754-2	Generic communication cable facilities	EN 50173-1:2007, ISO / IEC 11801:2002
------------------------	----------------	--	---------------------------------------

Electrical properties

Insulation strength	5000 MΩ
---------------------	---------

Cable structure

Wire material	Non-insulated copper wire	Standard designations	IE-7IC4x2xAWG23/1-PVC 02YSCY PIMF, S/FTP
Strands	1	Cross-section	4*2*AWG 23/1 - 4*2*0.255 mm ²
Insulation	PE	Insulation cross-section	1.4 mm
Number of wires	8	Arrangement of wire cores	Twisted pair
Wire pair shielding		Colour sequence or wires - wire pairs	white - blue, white - orange, white - green, white - brown
Shielding	Aluminium foil	Complete shielding	Shielding braid made from copper wiring
Shielding braid thickness	S/FTP 0.1 mm	Material sheath	PVC
Sheath diameter, min.	8 mm	Sheath diameter, max.	8.4 mm
Sheathing colour	green (RAL 6018)		

Electrical properties of cable

Category	Cat.7 (ISO/IEC 11801)	Test voltage: wire-wire-shield	700 V AC
Characteristic impedance	100 ± 5 Ω at 100MHz	Loop resistance	150 Ω/km
Deviation	5 ns/100m	Insulation strength	5000 MΩ
Capacity at 1 kHz	45 nF/km	Signal propagation time	4.5 ns/m

Mechanical and material properties of cable

Colour	green	Min. bending radius, once only	5 x cable diameter
Min. bending radius, repetitive	10 x cable diameter	Abrasion resistance	good
Resistance to spread of flame	in accordance with IEC 60332-1	UV-resistant	Yes
Silicone-free	Yes	Corrosiveness of fumes	to IEC 60754-2

Classifications

ETIM 6.0	EC000830	ETIM 7.0	EC003249
eClass 9.0	27-06-18-05	eClass 9.1	27-06-90-90
eClass 10.0	27-06-18-01	UNSPSC	26-12-16-06

Creation date May 1, 2020 4:16:56 AM CEST

Data sheet**Industrial Ethernet
IE-C7BS8VG-MW**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data**Approvals**

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 9 IETH 18/19 EN FL FIELDWIRING EN PI PROFINET CABLING EN
User Documentation	MAN IE GUIDE DE MAN IE GUIDE EN


Data sheet

**Industrial Ethernet
IE-C7BS8VG-MW**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Detailed drawing



**Industrial Ethernet
IE-C7BS8VG-MW**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

Tools



The CST with blue blade cartridge produces the best stripping results. The blue double-stage blade cartridge is particularly suited for Ethernet cables. It saves time and also ensures optimal stripping results.

General ordering data

Type	IE-CST	Version
Order No.	9204350000	Tools, Sheathing strippers, Coaxial data and round cables
GTIN (EAN)	4032248653072	
Qty.	1 pc(s).	

Tools

Sheathing stripper for PVC cables



General ordering data

Type	AM 12	Version
Order No.	9030060000	Tools, Sheathing strippers, UTP and STP data cables
GTIN (EAN)	4008190337827	
Qty.	1 pc(s).	