

Tools
POWERSTRIPPER AO 2,5-20

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



- for automatic stripping of individual wires
- stripping of flexible wires according to DIN VDE 0295, Cl. 5
- Partial stripping of insulation, the isolation remains on wire end
- Change of tools not necessary
- Quick and easy setting for the proper cross-section
- Stripping length from 3 to 20 mm
- Min. conductor length: 22 mm + stripping length
- Electric drive

General ordering data

Type	POWERSTRIPPER AO 2,5-20
Order No.	9027270000
Version	Automatic machines, Automatic stripper
GTIN (EAN)	4032248285402
Qty.	1 pc(s).

Data sheet

Tools POWERSTRIPPER AO 2,5-20

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Width	190 mm	Width (inches)	7.48 inch
Height	205 mm	Height (inches)	8.071 inch
Depth	295 mm	Depth (inches)	11.614 inch
Weight	9 kg	Net weight	8,500 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Technical data

Electrical connection 100-240 V / 50/65 Hz

Automatic stripping

Conductor length, min.	22 mm + stripping length	Connection values	46 VA
Drive	electrical	Electrical connection	100-240 V / 50/65 Hz
Pull-off length	1-20 mm	Pulse time	approx. 0.5 s
Stripping range	0.5 - 2.5 mm ² (~AWG 20-14)		

Classifications

ETIM 6.0	EC002778	ETIM 7.0	EC002778
eClass 9.0	17-13-01-01	eClass 9.1	17-13-01-02
eClass 10.0	17-13-01-02	UNSPSC	27-11-28-14

Approvals

Approvals



ROHS Conform

Downloads

Brochure/Catalogue	CAT 6 TOOLS 15/16 EN
Engineering Data	WSCAD
User Documentation	Manual

Data sheet**Tools**
POWERSTRIPPER AO 2,5-20

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Accessories**Accessories / replacement parts**

- for automatic stripping of individual wires
- stripping of flexible wires according to DIN VDE 0295, Cl. 5
- Partial stripping of insulation, the isolation remains on wire end
- Change of tools not necessary
- Quick and easy setting for the proper cross-section
- Stripping length from 3 to 20 mm
- Min. conductor length: 22 mm + stripping length
- Electric drive

General ordering data

Type	AIMESA VRM 2,09	Version
Order No.	1120920000	Automatic machines, Set of cutters
GTIN (EAN)	4032248901869	
Qty.	1 pc(s).	