

CUTTER 20 A**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Cutting tools for conductors up to 8 mm, 12 mm, 14 mm and 22 mm outside diameter. The special blade geometry allows pinch-free cutting of copper and aluminium conductors with minimum physical effort. The cutting tools also come with VDE and GS-tested protective insulation up to 1,000 V in accordance with EN/IEC 60900.

General ordering data

Type	CUTTER 20 A
Order No.	9040140000
Version	Cutting tool for one-hand operation
GTIN (EAN)	4008190467098
Qty.	1 pc(s).

Creation date May 1, 2020 2:33:22 AM CEST

CUTTER 20 A**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data**Dimensions and weights**

Width	245 mm	Width (inches)	9.646 inch
Height	71.5 mm	Height (inches)	2.815 inch
Depth	31 mm	Depth (inches)	1.22 inch
Weight	501 g	Net weight	443.7 g

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical data

Version	One-hand mechanical
---------	---------------------

Cutting tools

Copper cable - flexible, max.	95 mm ²	Copper cable - flexible, max. (AWG)	3/0 AWG
Copper cable - solid, max.	25 mm ²	Copper cable - solid, max. (AWG)	3 AWG
Copper cable - stranded, max.	50 mm ²	Copper cable - stranded, max. (AWG)	1 AWG
Copper cable, max. diameter	22 mm	Data / telephone / control cable, max. Ø	22 mm
Single-core aluminium cable, max.(mm ²)	50 mm ²	Stranded aluminium cable, max (mm ²)	70 mm ²
Stranded aluminium cable, max. (AWG)	2/0 AWG	Stranded aluminium cable, max. diameter	22 mm

Classifications

ETIM 6.0	EC000142	ETIM 7.0	EC000142
eClass 9.0	21-04-47-01	eClass 9.1	21-04-37-06
eClass 10.0	21-04-47-01	UNSPSC	31-16-31-02