

Accessories UBH SWH 1/4 EC 6.3

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com







The Weidmüller bits are standard bits which are highly popular with users thanks to their good quality, large range and efficiency. The computer-controlled hardening method enables Weidmüller to guarantee a consistently high standard of quality.

The high-quality raw materials used make it possible to reach torques far higher than any of those specified in the relevant DIN standards:

- DIN 5261 for PH/PZ bits,
- DIN 5263 for slotted bits,
- Camcar standard for TORX bits

That means a long life at high torques and hence ideal conditions for standard situations.

The benefits:

- Suitable for all types of screws. Because of their excellent hardness values of 59-61 HRC, they are suitable for use with both manual and power tools.
- Good wearing resistance and thus a long life expectancy.
- Optimum fit in all DIN screws means low wear and optimum torque transmission.
- Manufactured to meet professional quality criteria according to relevant ISO standards with a consistently high standard of quality.

General ordering data

Туре	UBH SWH 1/4 EC 6.3
Order No.	<u>9205680000</u>
Version	Mounting tool
GTIN (EAN)	4032248772988
Qty.	1 pc(s).



Accessories UBH SWH 1/4 EC 6.3

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

-			
Dim	ensions	and	weights

Width	60 mm	Width (inches)	2.362 inch
Weight	30 g	Net weight	34.7 g
Environmental Produ	ıct Compliance		
DE 1 011 01 // 10			
REACH SVHC	Lead 7439-92-1		
Technical data			
Version	Universal quick release holder with locking function		
Screwing tools			
Form	E 6.3 DIN 3126		
Classifications			
ETIM 6.0	EC002118	ETIM 7.0	EC002118
eClass 9.0	21-04-92-90	eClass 9.1	21-01-90-90
eClass 10.0	21-04-92-90	UNSPSC	27-11-28-15

Downloads

ROHS

Brochure/Catalogue	<u>CAT 6 TOOLS 15/16 EN</u>	

Conform