

**Testing tools
VT CTB**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The main function of the voltage tester is to establish if voltage is present. A 2-pole voltage tester is the only approved testing instrument that fulfils the requirements of work protection regulations.

- with LED-Display
- acc. to VDE standard
- high peak voltage strength
- the right tester for every application

General ordering data

Type	VT CTB
Order No.	9918970000
Version	2-pole voltage tester, No
GTIN (EAN)	4032248405855
Qty.	1 pc(s).

Creation date April 30, 2020 7:17:01 PM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

Data sheet

**Testing tools
VT CTB**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Width	137 mm	Width (inches)	5.394 inch
Height	21 mm	Height (inches)	0.827 inch
Depth	19 mm	Depth (inches)	0.748 inch
Weight	50 g	Net weight	50 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Measuring and testing devices

AC voltage measuring range	3-48 V	Continuity test	No
DC voltage measuring range	48 V	Display	LED
Frequency range, max.	65 Hz	Frequency range, min.	0 Hz
Protection degree	IP40	Rated voltage, max.	48 V DC
Rated voltage, min.	3 V DC	Tested and approved according to	EN 61010-1, EN 61326
Working temperature, max.	50 °C	Working temperature, min.	-10 °C

Classifications

ETIM 6.0	EC000494	ETIM 7.0	EC000494
eClass 9.0	27-20-03-08	eClass 9.1	27-20-03-08
eClass 10.0	27-20-03-08	UNSPSC	41-11-36-37

Approvals

Approvals



ROHS Conform

Downloads

Brochure/Catalogue [CAT 6 TOOLS 15/16 EN](#)
 User Documentation [Manual](#)

**Testing tools
VT CTB**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

